

General Reenactor Artillery Safety Test (ver 3/4/2006)

1. The minimum Battlefield Side Safety Zone between a loaded artillery piece and any other non-crew person is:
 - a. 5 yards
 - b. 10 yards
 - c. 15 yards
 - d. 20 yards
2. The minimum Battlefield Safety Zone between an open pass box or limber and any other non-crew member is:
 - a. 5 yards
 - b. 10 yards
 - c. 15 yards
 - d. 20 yards
3. The minimum Battlefield Safety Zone between the front of a loaded artillery piece is:
 - a. 5 yards
 - b. 10 yards
 - c. 15 yards
 - d. 20 yards
4. Implements placed vertically on the hubs or wheels of artillery piece wheels indicate that:
 - a. The gun is loaded
 - b. The gun is empty
 - c. The gun has misfired
5. Implements held over the artillery piece in an "X" indicate:
 - a. The gun is loaded
 - b. The gun is empty
 - c. The gun has misfired
6. The minimum Battlefield Safety Zone in front of an artillery piece that has misfired is:
 - a. 5 yards
 - b. 10 yards
 - c. 15 yards
 - d. 20 yards
7. Immediately prior to the command "Fire", the Chief of the Piece will call:
 - a. "Ready" and/or "Clear Front"
 - b. "On Your Mark"
 - c. No preparatory command is given

THANK YOU FOR TAKING THIS TEST. BE CAREFUL AND SAFE!

You need at least 100% correct to pass Pass ____ Fail ____